

# Z-GET74

This chapter covers the following topics:

- Description
  - Parameters
  - Return Codes
  - Subprograms
- 

## Description

Return information about an external node which uses either the transport service or the spool file.

## Parameters

| Parameter        | Format   | In | Out | Remarks  |
|------------------|----------|----|-----|--|
| Return-code      | N2       |    | X   |  |
| Node-name        | A8       | R  |     | The name of the external node.   |
| Node-description | A40      |    | X   | The description of the external node.  |
| Node-type        | A1       |    | X   | A=remote Con-nect node, B=Telex, F=SNADS, G=printer, H=Telefax, T=Teletex, U=Lotus AU/Con-nect: Internet E-mail.   |
| Address-level    | N1       |    | X   | The address level establishes limitations for the Send function. A value between 0 (lowest level) and 9 (highest level).   |
| Destination-node | A8       |    | X   | Only returned for a node which uses the transport service. The name by which the node is identified by the transport service.  |
| Node-parameters  | A250/1:7 |    | X   | The physical address of the external node. See <i>External Communication</i> . For a node which uses the spool file, only the first occurrence of the Node-parameters is used. |

## Return Codes

|    |                     |
|----|---------------------|
| 00 | Success             |
| 93 | Node does not exist |

## Subprograms

Z-191

